




APEX
GASGEN

The Nevis 40C



Description

High purity nitrogen is delivered as and when required. Featuring integral Jun Air compressors Nevis 40C Generator provides a true stand-alone solution. All models in the range are mobile to allow easy repositioning and installation.

All of the units in the range are built on a modular design to allow the capacity to be expanded upon if required. As with most of our products, there is the option for bespoke models which better fix your laboratories needs, flow rates, purity levels, connection ports, integrated compressors and more are all to be customised to best suit your requirements.

The Nevis 40C supplies you with high purity nitrogen as and when it is required and is manufactured to use Pressure Swing Adsorption (PSA) technology which provides you with the purest form of nitrogen available in a continuous supply all at the best industrial price for your application. Apex aims to provide you with a system which offers efficiency for the ideal performance time and time again.

Features & Benefits

- Standard flow rates of up to 25litres/min
- Output pressure 5.4 Barg / 80psig
- High purity Nitrogen up to 99.9995%
- Medical grade tubing as standard
- Stand-by mode
- PSA technology
- Built in oil-free compressor to reduce contaminants
- Easy installation
- Simple and low cost maintenance






Technical Specifications

Model	Nevis 40C
Flow / Min	40
Purity (% N2)	Up to 99.9995%
Dew Point (°C)	- 40
Power Consumption (W)	4000
Voltage (V AC)	400 3 phase or 240 single phase
Depth (mm / inch)	650 / 25.6
Height (mm / inch)	1650 / 65
Width (mm / inch)	1130 / 44.5
Weight (kg / lbs)	251 / 553
Connection Ports	Female 1/4 BSPP
Max Altitude (m)	2000
Particulates (um)	<0.01
Lubricants	None
Output Pressure (Barg/Psig)	5.4 / 80
Humidity	80% up to 31°C decreasing linearly to 50% at 40°C

How It Works

Air from an external source enters the generator via a 0.01-micron filter [1] that removes contaminants and bulk moisture via an integrated auto drain. When the control system assesses that more nitrogen is required, the solenoid valve [2] is opened and pressure is allowed to build in the column [4] containing Carbon Molecular Sieve (CMS) and a residue moisture catcher [3]. This sieve adsorbs the oxygen and leaves the dry nitrogen free to flow through the non-return valve into the direction of the variable reservoir capacity (VRC) [7]. Following on from this the Nitrogen is allowed to flow to the application via another 0.01-micron filter [8] and pressure and flow regulators [9]. The trapped oxygen is meanwhile filtered out through the exhaust valves [6]





Applications

- Vessel Leak Detection
- Ionisation (API-ms)
- GC-FID (Carrier gas)
- GC-FID (Make-up gas)

Warranty

All Apex units are supplied with our standard 1 year warranty. Accompanied with our on-going care and servicing facilities Apex provides the highest quality peace of mind.



Contact Details

Apex Gasgen Ltd
Unit 36 Elderpark Workspace
Elderpark Street
Glasgow G51 3TR
Scotland

Tel: +44 (0) 141 530 7417
Email: karen@apexgasgenerators.com
Web: www.apexgasgenerators.com